



MATERIAL SAFETY DATA SHEET

Manufacturer : NIPPON PAINT (S) CO., PTE LTD
 Address : No.1 First Lok Yang Road
 Jurong, Singapore 629728
 Telephone : 6265 5355 Ext. Technical Department
 Date : 19 October 1997
 Last Updated : 10 May 2005

SECTION I - PRODUCT IDENTIFICATION

Product Name : Nippon Vinilex 120 Active Primer
 Product Class : 2-pack Solvent-based Polyvinyl Butyral Resin Paint
 Reference : MSDS-047

SECTION II - CHEMICAL INGREDIENTS

<u>Components</u>	<u>Weight(%)</u>
Base	
Resin	Polyvinyl Butyral / Phenolic Resin 50.0 - 60.0
Additive	Oxidised Polyethylene 1.0 - 2.0
Pigment	Carbon Black) 10.0 - 15.0
	Chrome Yellow)
	Talc)
	Zinc Chromate)
Solvents	Alcohol) 20.0 - 30.0
	Toluene)
	Ketone)
	<u>Hardener</u>
Alcohol)	
Phosphoric Acid)	100.0
Water)	

SECTION III - HAZARD IDENTIFICATION

- Contain Lead and Chrome compound.
- Keep away from foodstuff and drinking water.
- Put on personal protective gears like goggles, gloves etc during handling.
- May produce toxic fumes of Chrome during a fire.
- May cause harm to unborn child.
- Contain volatile and inflammable solvent; ensure adequate ventilation during use and avoid using near ignition sources.

SECTION IV - PHYSICAL AND CHEMICAL DATA

	<u>Base</u>	<u>Hardener</u>
Appearance :	Matt Olive Green	Clear
Viscosity :	58 - 62 Ku at 25°C	-
Specific Gravity (H ₂ O=1) :	0.90 - 0.96 at 25°C	0.84 - 0.90 at 25°C
Non-volatile :	Above 20.0% by weight	-
Flash Point :	5°C	25°C
Pot Life (after mixed) :	18 hours at 30°C. Pot life is shorter at higher temperature.	
Shelf Life :	9 months in sealed original packaging stored at room temperature (25 - 28°C)	

SOLVENT-BASE PRODUCT
WITH LEAD & CHROME

Product Name : Nippon Vinilex 120 Active Primer

SECTION V - FIRE AND EXPLOSION HAZARD DATA

Extinguishing Media	:	Foam / Dry Chemical / Carbon Dioxide
Special Fire Fighting Procedure	:	Cool closed containers with water spray; isolate from heat, electrical equipments, sparks and open flame; fire fighters use protective apparatus.
Unusual Fire and Explosion Hazards	:	Closed containers may explode when exposed to extreme heat; avoid spreading burning liquid with water for cooling; isolate.

SECTION VI - HEALTH HAZARD DATA

Effects of Over Exposure:-

Inhalation	:	Respiratory irritation, headache and nausea
Eye Contact	:	Cause severe eye irritation and blurred vision
Skin Contact	:	May cause moderate skin irritation
Ingestion	:	Harmful if swallowed.
Delayed Effects	:	None currently known.

Emergency and First Aid Procedures:-

Inhalation	:	Remove to fresh air
Eye Contact	:	Flush eyes thoroughly with plenty of clean water for at least 15 minutes; obtain medical care.
Skin Contact	:	Remove promptly by wiping followed by washing with soap and water.
Ingestion	:	Get immediate medical help; do not induce vomiting.

SECTION VII - REACTIVITY DATA

Stability	:	Stable
Conditions to Avoid	:	Do not expose to heat or ignition sources.
Hazardous Decomposition Products	:	Toxic fumes of Lead and Chrome during a fire.
Hazardous Polymerisation	:	Will not happen.
Incompatibility (Materials to Avoid)	:	None.

SECTION VIII - SPILL OR LEAK PROCEDURE

Steps To Be Taken In Case Material Is Released Or Spilled:

Provide ample ventilation. Remove potential sources of ignition. Put on personal protective gears like respirator, goggle and gloves. Major and minor spills should be collected using the suitable absorbent for disposal. Prevent from entering sewers or watercourses.

Waste Disposal Method: Must be disposed in accordance with appropriate government regulation.

SOLVENT-BASE PRODUCT
WITH LEAD & CHROME

Product Name : Nippon Vinilex 120 Active Primer

SECTION IX - SPECIAL PROTECTION INFORMATION

Ventilation : General / local exhaust ventilation is expected to be satisfactory.

Respiratory Protection : NIOSH-approved respirator with organic vapour cartridges recommended.

Protective Gloves : Solvent resistant type recommended.

Eye Protection : Safety glasses / goggles with side shields recommended

Other Protective Equipment : Eye bath; readily accessible.

SECTION X - SPECIAL PRECAUTION

Handling and Storing : Keep container closed, have adequate ventilation, avoid sources of heat, sparks and flame.

Other Precaution : Avoid contact with eyes, skin and prolong breathing of vapour.

SECTION XI - MISCELLANEOUS INFORMATION

Note to Physician : The material contains Lead and Chrome Compound.

Remark : The information contained herein is to the best of our knowledge and believe accurate. However, the information is provided without any representation or warranty, expressed or implied, regarding its accuracy or completeness. Since the conditions of handling, storage, use and disposal are beyond our control and may be beyond our knowledge, for this and other reasons, we make no guarantee of results and assume no liability for damages incurred by the use of this product. Please be reminded that all chemicals may present unknown health hazards and should be used with caution.